


FRONT END CYLINDER

TRUNNION - EYE



5F1335196601AN - 5F-06660-196-6-M1428-0000N

Tipping weight 48-85 ton (**)

Extension	1	2	3	4	5	6	7	8	9	10	Maximum pressure 220 bar
Rod diameter [mm]	196	174	154	135	116	98					No. 6 telescopic extensions
Stroke length [mm]	1102	1106	1107	1115	1115	1115					Total stroke length: 6660 mm
Oil [dm³]	33.2	26.3	20.6	15.9	11.8	8.4					Working volume 116,2 dm³ Residual volume 8,9 dm³
Thrust [kN] at p max	664	523	410	315	233	166					Max cylinder load - Start tipping 245 kN
											Critical buckling load fully extended 247 kN (327 bar)
Technical notes											Guide kit: K15F001966001 - Seal kit: K25F001966001

* Mounting dimensions 1428 including 20 (-5;+30) mm pull out

Max pump flow 220 L/min with end of stroke

Weight 300 kg

Seal ring: Temperature range (-40; +100) °C - Maximum linear speed 0.5 m/s

Max pump flow 162 L/min without end of stroke

Tipping time at flow max 32 s

Enamel RAL9005 two-component solvent semi-gloss finish minimum thickness 60 m 180 h spray salt test ISO 9227 rating 9 ISO 10289

Chrome coating type CRN on rod stage 40 h spray salt test ISO 9227 rating 9 ISO 10289

All the information here reported are intended for further investigations by users with technical knowledge. The user, as manufacturer of the completed machinery which will incorporate the here described components, is the solely responsible for the final selection of the components. The user must carry out necessary research and tests on components to determine whether, by its design and construction, all performance, endurance, maintenance, safety and warning requirements are met. The user must assure the compliance of the completed machinery with all appropriate laws, directives, norms, industry standards. The cylinder has been designed to provide only a linear pushing force. The cylinder is not a structural member and must not be used as a stabilizer or be subject to side or pulling load. The cylinder will not prevent the dump body or trailer from rollover or lateral tilt. Cylinder rated pressure reflect only the capability of the pressure-containing envelope and not the force transmitting capability of mounting configurations. The ordinary use of telescopic cylinder will not require any coating since the telescopic stages are exposed to atmospheric agents only during the tip-up operation, if duration is below 2 hours.

(**) Tipping weight calculation-The body weight plus the max payload are the max tipping weight that can be raised by the cylinder. This value, calculated at the max pressure, is a rough indication of the tipping power of the cylinder and must be used as a first criteria for the selection of the cylinder. The real tipping mass can only be calculated by the design engineer of the completed machinery, and must take into account the geometry of the dump body, the operating conditions and all the reasonably foreseeable uses.

Related documentation

11/01/2023

Read and understand Mounting instructions, User manual, Oil specifications, User responsibility before use

rev. 1 - 2023.01.11 - MP